



PRV654KLEDHDBT

65" 4K Ultra High Resolution Commercial Grade HDBaseT LED-LCD Monitor

Slim & Reliable- This 24/7 rated display features true 4K 3840 x 2160 resolution providing a strikingly clear image.

Direct LED – This new display features direct LED backlighting for a more uniform looking monitor with lower power consumption.

Applications – High Tech Conference Room, Digital Signage, Control Rooms, Broadcast, Gaming, Hospitality, Retail, Higher Education, Corporate, Healthcare and Industrial.

Highlights

- 65" true 4K industrial display with *metal frame housing*
- New Direct LED 450 NITS backlight
- Internal upscale capability from FHD to UHD
- Direct HDBaseT Input
- Wired for ultra 4K HD resolution with HDMI and Display Port
- Super thin ADA compliant depth
- Optional Multi- Touch Technology
- Heat Control – sensors monitor internal temperature allowing remote control of fans
- Industrial reliability (50,000 hours)

Technical Specification

Display	Screen Size	65"
	Aspect Ratio	16:9
	Resolution	3840 x 2160 (QWUXGA)
	Refresh Rate	120Hz
	Response Time (ms)	5
	Brightness	450 cd/m2
	Contrast Ratio	3500:1
	Viewing Angle	178° / 178°
	Colors	1.07 Billion (10 BIT)
Connectivity	USB	Software Updates
	RS-232	1 x Input
	HDBaseT	1 x Input
	DVI-D	1 x Input
	HDMI 1	1 x Input
	HDMI 2 - MHL	1x Input
	RGB Analog (VGA)	1 x Input
	Audio IN	For DVI and PC source
	HDMI 1.4 (3840 X 2160)	1 x Input
	Display Port (3840 X 2160)	1 x Input
	AC Power	1 x Input
Power	Requirements	AC 90~240V @ 50/60Hz
	Standby Consumption	3W
	Operating Consumption	200W
Environmental	Operating Temperature	0°-40° C
	Operating Humidity	10% - 90%
General	Dimensions	56.8" x 32.34" x 2.64"
		144.3 x 82.16 x 6.74 cm
	Packing Dimensions	71" x 45" x 12"
		180.3 x 114.3 x 30 cm
	Weight	110 lbs
50Kg		
VESA Dimensions	600 x 400 mm	

Mechanical Drawing

