



Light weight of 6.5kg / 14.33lbs.

### PRODUCT HIGHLIGHTS

- >1920 HZ RATE OF RENUAL
- 24/7 INDUSTRIAL RATED
- 100,000 LED LIFESPAN
- 170 / 140 H/V VIEWING ANGLE
- 800 NITS OF BRIGHTNESS
- 5 YEAR PARTS & LABOR WARRANTY

### PRIMEVIEW CUSTOMER SUPPORT

PRIMEVIEW'S ENGINEERING AND INSTALLATION TEAM IS DEDICATED TO MEETING CLIENTAL NEEDS. WE DEVOTE OURSELVES TO SUPPORTING AND GIVING THE HIGHEST QUALITY SERVICE IN CONSULTATION, INSTALLATION, AND AESTHETIC.

## SPECIFICATIONS

	EPIC 1.9MM	EPIC 2.6MM	EPIC 3.1MM	EPIC 3.9MM
MODEL #	PRVLEDEPC19	PRVLEDEPC26	PRVLEDEPC31	PRVLEDEPC39
LED TYPE	SMD	SMD	SMD	SMD
PIXEL DENSITY	262,144	147,456	102,400	65,536
VIEWING ANGLE (H/V)	170 / 140	170 / 140	170 / 140	170 / 140
BRIGHTNESS (CD/SQ.M.)	800	800	800	800
REFRESH RATE	>1920	>1920	>1920	>1920
OPTIMIZED VIEWING DISTANCE (M)	1.9~30	2.6~39	3.1~47	3.9~60
AVERAGE POWER CONSUMPTION	200	200	200	200
MAXIMUM POWER CONSUMPTION	624	624	624	624
INPUT VOLTAGE	AC 90 V - AC 264V± 10% 50/60Hz	AC 90 V - AC 264V± 10% 50/60Hz	AC 90 V - AC 264V± 10% 50/60Hz	AC 90 V - AC 264V± 10% 50/60Hz
MODULE SIZE IN PIXEL (WXH)	128X128	96X96	80X80	64X64
PANEL SIZE IN PIXEL (WXH)	250X250	250X250	250X250	250X250
PANEL SIZE IN MM (WXHXD)	500X500X80	500X500X80	500X500X80	500X500X80
WEIGHT (KG/SQ.M.)	26	26	26	26
IP RATING	IP40 FRONT / IP40 REAR	IP40 FRONT / IP40 REAR	IP40 FRONT / IP40 REAR	IP40 FRONT / IP40 REAR
PROCESSING	19 BIT	19 BIT	19 BIT	19 BIT
MAINTENANCE	FRONT/REAR	FRONT/REAR	FRONT/REAR	FRONT/REAR
OPERATING TEMPERATURE	-10°C~ 40°C	-10°C~ 40°C	-10°C~ 40°C	-10°C~ 40°C
OPERATING HUMIDITY	10~90RH%	10~90RH%	10~90RH%	10~90RH%